

SLIM MINI APPLIQUE



MONO EMISSION


PERFORMANCE DATA

TRUE POWER (W)	11.5
TRUE LUMENS (3000K)	1093 (.20)
TRUE LUMENS (4000K)	1155 (.20)
L90 LIFETIME (HRS)	72.000 (Ta 35°C)

BUILD DATA

CLASS	I
NOMINAL VOLTAGE	220-240V 50/60Hz
POWER SUPPLY	INCLUDED ON-OFF
EXTERNAL CABLE	SINGLE INPUT
	NOT PRESENT
PROTECTION RATING	IP66 - IK08


DIMENSIONS



DOUBLE EMISSION

22.0
2157 (.20)
2278 (.20)
72.000 (Ta 35°C)

I
220-240V 50/60Hz
INCLUDED ON-OFF
SINGLE INPUT
NOT PRESENT
IP66 - IK08



CODE COMPOSITION

● FINISH

■ LED COLOR

▲ BEAM

30905	● ■ ▲
.1 - ANTHRACITE	
.2 - PURE WHITE (RAL9010)	
.4 - ALU GREY (RAL9006)	
.8 - DARK BROWN	
.2 - 2700°K - CRI > 80	
.3 - 3000°K - CRI > 80	
.4 - 4000°K - CRI > 80	
.20 - 20° NARROW	
.50 - 35° MEDIUM	
.06 - ASYMMETRICAL	
.07 - WALL WASHER	

30927	● ■ ▲
.1 - ANTHRACITE	
.2 - PURE WHITE (RAL9010)	
.4 - ALU GREY (RAL9006)	
.8 - DARK BROWN	
.2 - 2700°K - CRI > 80	
.3 - 3000°K - CRI > 80	
.4 - 4000°K - CRI > 80	
.20 - 20° NARROW	
.50 - 35° MEDIUM	
.06 - ASYMMETRICAL	
.07 - WALL WASHER	